


ISM



Performance Summary

Parameter	Min.	Тур.	Max.	Units	Note
Power Out @ 3dB _c	900	1000		W	
Frequency Range	1.5	5/0/	30	MHz	
AC Voltage Supply	180	230	264	V_{ac}	
Current Absorption @ 1000W @ 230V _{ac}			15	Α	9
Power Gain@ 3dB _c		60		dB	90
Gain Flatness @ 3 dB _c		± 3		dB	
Harmonics Level		2/ /	-10	dB _c	20/// 8
Nominal Power In		1		mW	/////
Input Return Loss		-15		dB	
Output Return Loss	1	-15	//(dB	

TDE1K0-HF-DW

Characteristics

TDE1K0-HF-DW is a high-power RF amplifier specifically designed for ISM applications in the frequency band 1.5 – 30 MHz.

TDE1K0-HF-DW is based on brand-new solid-state devices which ensure the highest power level on the market.

The amplifier works in AB class.

MAIN FEATURES

- High Ruggedness
- Touch-screen display
- Self-protected against:
 - i. Abnormal temperature
 - ii. Abnormal reflected power
 - iii. Abnormal current absorption
 - iv. Overdrive
- Telemetry includes:
 - i. Forward and Reflected RF power
 - ii. DC Voltage
 - iii. Temperature
 - iv. Alarm Status

AC and RF Connectors

Notes












www.tdeitaly.com (+39)

(+39) 0765484028



ISM

(*) On request, the amplifier might be equipped by

- WEB Interface
- SNMP

- RF Out: DIN 7/16 female
- RF In: SMA female
- **FWD_Probe:** SMA female (optional)
- RFL_Probe: SMA female (optional)
- AC In: Pluggable Terminal Blocks 5 positions 7.62 mm

General Specifications

- Dimensions (LxWxH): 483x613x441 mm
- Weight: 20 Kg
- Ambient Temperature: 0 ~ +45 °C
 Storage Temperature: -20 ~ +85 °C
- Relative Humidity: up to 95% (not condensing)
- Operating Altitude: up to 2000 meters above sea level
- Cooling: Forced air with integral blowers (air intake from front, air exhaust at rear)

TDE reserve the right to make changes to the product(s) or information contained herein without notice. TDE doesn't assumes responsibility for any errors which may appear in this document. Warranty information applicable to the product identified here in is available upon request. Nothing contained herein shall constitute a warranty, representation or guarantee of any kind. TDE expressly disclaims all other warranties, express and/or implied including but not limited to warranties of merchantability, and of fitness for a particular purpose, use or application.

No part of this document may be copied or reproduced in any form or by any means without the prior written consent of TDE.







